Environmental Product Declaration according to ISO 14025 and EN 15804



This declaration is for: Spenner CEM I 52,5 N (tu)

Provided by: **Spenner Zement**





program operator
Stichting MRPI®
publisher
Stichting MRPI®
www.mrpi.nl

MRPI® registration
1.1.00083.2019
EPD registration
00001065
date of first issue
16-12-2019
date of this issue
16-12-2019

expiry date 16-12-2024











PROGRAM OPERATOR

Stichting MRPI® Kingsfordweg 151 1043GR Amsterdam

Spenner Zement

Hüchtchenweg 2

0049 2943 9860

59597

Erwitte



COMPANY INFORMATION

spenner



PRODUCT

Spenner CEM I 52,5 N (tu)



MRPI® REGISTRATION

1.1.00083.2019



EPD REGISTRATION

00001065



DATE OF ISSUE

16-12-2019



EXPIRY DATE

16-12-2024



DECLARED UNIT/FUNCTIONAL UNIT

tonne



SCOPE OF DECLARATION

info@spenner-zement.de https://spenner-zement.de/

This MRPI®-EPD certificate is verified by Niels Jonkers, Ecochain.

The LCA study has been done by Pieter Stadhouders, EcoReview.

The certificate is based on an LCA-dossier according to ISO14025 and NEN-EN15804+A1. It is verified according to the 'EPD-MRPI verification protocol May 2017'. EPD's of construction products may not be comparable if they do not comply with NEN-EN15804+A1. Declaration of SVHC that are listed on the 'Candidate List of Substances of Very High Concern for authorisation' when content exceeds the limits for registration with ECHA.



VISUAL PRODUCT



DESCRIPTION OF PRODUCT

Portland cement



MORE INFORMATION

https://spenner-zement.de/produkte/zement/port landzement-cem-i-525-n-tu/



DEMONSTRATION OF VERIFICATION

CEN standard EN15804 serves as the core PCR[a]

Independent verification of the declaration and data, according to EN ISO 14025:2010:

internal:

external: X

(where appropriate[b]) Third party verifier:



[a] Product Category Rules [b] Optional for B-to-B communication, mandatory for B-to-C communication (see EN ISO 14025:2010, 9.4).







DETAILED PRODUCT DESCRIPTION

Product name: Spenner CEM I 52,5 N (tu)

Portland cement, sold in bulk quantities. The production processes needed to come to this product are grinding and mixing. The clinker that is used as the main ingredient is self produced. For this, mining, transport, breaking, drying and calcination has been performed.

This product is an intermediate product for making cementitious-bound materials.

COMPONENT (> 1%)	[kg / %]
Anhydrite	3.40%
Iron sulfate	0.45%
Gypsum	1.50%
Limestone	0.10%
Clinker	94.46%
BASF GA 1150 (grinding additive)	0.09%

(*) > 1% van total mass



This product is produced in Erwitte (Germany). It is applied as an intermediate product for cementitious-bound materials.

Analysis has been done using the Ecochain software. Ecoinvent V3.4 was used for the analysis. It is an intermediate product and therefore end-of-life scenarios are not clear. The specific EPD only covers A1-A3.

PRODUCT STAGE CONSTRUCTION					USE STAGE							ND OI	F LIFE		BENEFITS AND			
PROCESS													STA	GE		LOADS BEYOND THE		
			ST.	AGE												SYSTEM BOUNDARIES		
Raw material supply	Transport	Manufacturing	Transport gate to site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment		Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Recovery- Recycling- potential		
A1	A2	А3	A4	A5	B1	B2	В3	B4	B5	B6	B7	C1	C2	C3	C4	D		
х	х	х	MNA	MNA	MNA	MNA	MNA	MNA	MNA	MNA	MNA	MNA	MNA	MNA	MNA	MNA		

X = Module assessed

MNA = Module not assessed









REPRESENTATIVENESS

Not applicable as this is an environmental product declaration for a specific product from a specific manufacturer on a specific location.



ENVIRONMENTAL IMPACT per functional unit or declared unit

	UNIT	A1	A2	А3	A1-A3	A4	A5	B1	B2	ВЗ	В4	B5	В6	В7	C1	C2	СЗ	C4	D
ADPE	kg	1.94	3.85	1.16	3.10	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
ADI L	Sb-eq.	E -1	E -6	E -1	E -1	IINA	IIVA	IIVA	IIVA	IIVA	IIIA	IIIA	IINA	IIVA	IIVA	IIVA	шил		
ADPF	MJ	1.69	2.08	2.11	1.92	INA	INA	INA	INA	INA	INA	IA INA	INA	INA	INA	INA	INA	INA	INA
ADII	IVIO	E +3	E +1	E +2	E +3		IIIVA	III	IIVA	IIVA	IIIA		IINA	IIVA	IIVA	IIVA	IIVA		
GWP	kg	7.82	1.35	1.75	8.01	INIA	NA INA	INA	INA	INA	INA	A INA	A INA	INA	INA	INA	INA	INA	INIA
GVVI	CO2-eq.	E +2	E +0	E +1	E +2	шлд		III	IIV	IIVA	IIV				IINA	IIVA	IIV		INA
ODP	kg	2.93	2.50	1.23	4.41	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
ODI	CFC11-eq.	E -6	E -7	E -6	E -6	IINA	IIIVA	III	1117	IIVA	IIVA	IIVA		IINA	IINA	IIVA	IIVA	IIIA	IIVA
POCP	kg	8.03	7.99	3.01	8.41	INA	NA INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
1 001	ethene-eq.	E -2	E -4	E -3	E -2	IINA	IIIVA	III	IIVA	IIVA	IIVA								IIIA
AP	kg	7.30	5.87	1.47	8.83	INAI	INA II	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
AF	SO2-eq.	E -1	E -3	E -1	E -1			IIVA	IIVA	IIVA									
EP	kg	2.20	1.17	3.11	2.52	.52 INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
	(PO4)3eq.	E -1	E -3	E -2	E -1	ПАЛ	114/-	A IIIVA	шил	ПАА	шил	IIVA	11 4/-1	IIVA	IIVA	IIVA	IINA	IINA	IIVA
Toxicity	indicators (Dι	ıtch mar	ket)																
HTP	kg DCB-eq.	2.37	5.42	2.96	2.72	INA	INA	INA	INA	INA	INA	A INA	INA	INA	INA	INA	INA	INA	INA
	kg bob cq.	E +1	E -1	E +0	E +1	П	114/-	11 1/7	ПУА	ПУА	шил			ш	ПУЛ	ПУЛ	шил	ш	INA
FAETP	kg DCB-eq.	6.69	1.59	5.64	7.41	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
. /	ng BOB cq.	E -1	E -2	E -2	E -1	11 47 (11 17 1	11 17 1	IINA	IINA	11 47 (11 17 1	11 1/ 1	11 1/ 1	11 47 (
MAETP	kg DCB-eq.	1.78	5.74	6.72	2.46	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
IVI/AL II	kg DOD cq.	E +4	E +1	E +3	E +4	П	114/-	11 1/7	ПУА	шил	шил	ш	IINA	IINA	IIVA	ПУЛ	шил	ш	114/
TETP	kg DCB-eg.	5.23	1.92	1.03	6.29	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
1211	ng DOD-eq.	E -1	E -3	E -1	E -1	11.47	111/	11.1/	11.1/	11.1/	11.1/	11.17	11.4/	11.4/	114/	114/	111/7	11.4/	11.4/
ECI	Euro	4.83	1.60	2.73	5.12	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
	Luio	E +1	E -1	E +0	E +1	1117	111/4	111/4	111/7	111/7	111/7	111/4	111/7	111/7	IIVA	IIVA	111/7	IINA	IIVA

ADPE = Abiotic Depletion Potential for non-fossil resources

ADPF = Abiotic Depletion Potential for fossil resources

GWP = Global Warming Potential

 $\label{eq:ode} \mathsf{ODP} = \mathsf{Depletion} \ \mathsf{potential} \ \mathsf{of} \ \mathsf{the} \ \mathsf{stratospheric} \ \mathsf{ozone} \ \mathsf{layer}$

POCP = Formation potential of tropospheric ozone photochemical oxidants

AP = Acidification Potential of land and water

EP = Eutrophication Potential

HTP = Human Toxicity Potential

FAETP = Fresh water aquatic ecotoxicity potential

MAETP = Marine aquatic ecotoxicity potential

TETP = Terrestrial ecotoxicity potential

ECI = Environmental Cost Indicator









RESOURCE USE per functional unit or declared unit

	UNIT	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	В4	В5	В6	В7	C1	C2	C 3	C4	D
PERE	MJ	1.39 E +2	2.85 E -1	1.10 E +2	2.49 E +2	INA	INA	INA											
PERM	MJ	0	0	0	0	INA	INA	INA											
PERT	MJ	1.39 E +2	2.85 E -1	1.10 E +2	2.49 E +2	INA	INA	INA											
PENRE	MJ	1.44 E +3	2.23 E +1	3.08 E +2	1.78 E +3	INA	INA	INA											
PENRM	MJ	0	0	0	0	INA	INA	INA											
PENRT	MJ	1.44 E +3	2.23 E +1	3.08 E +2	1.78 E +3	INA	INA	INA											
SM	kg	0	0	0	0	INA	INA	INA											
RSF	MJ	0	0	0	0	INA	INA	INA											
NRSF	MJ	0	0	0	0	INA	INA	INA											
FW	m3	8.01 E -1	4.01 E -3	8.21 E -2	8.87 E -1	INA	INA	INA											

INA = Indicator Not Assessed

PERE = Use of renewable energy excluding renewable primary energy resources

PERM = Use of renewable energy resources used as raw materials

PERT = Total use of renewable primary energy resources

PENRE = Use of non-renewable primary energy resources excluding non-renewable energy resources used as raw materials

PENRM = Use of non-renewable primary energy resources used as raw materials PENRT = Total use of non-renewable primary energy resources

CC . Her of receivable accordent finds

SM = Use of secondary materials

NRSF = Use of non renewable secondary fuels

RSF = Use of renewable secondary fuels

FW = Use of net fresh water



OUTPUT FLOWS AND WASTE CATEGORIES per functional unit or declared unit

	UNIT	A1	A2	А3	A1-A3	A4	A5	B1	B2	В3	B4	B5	В6	В7	C1	C2	C3	C4	D
HWD	kg	2.96 E -2	1.54 E -4	2.69 E -3	3.24 E -2	INA													
NHWD	kg	7.51 E +0	1.28 E +0	1.07 E +0	9.86 E +0	INA													
RWD	kg	2.75 E -3	1.41 E -4	1.64 E -3	4.53 E -3	INA													
CRU	kg	0	0	0	0	INA													
MFR	kg	0	0	0	0	INA													
MER	kg	0	0	0	0	INA													
EEE	MJ	0	0	0	0	INA													
ETE	MJ	0	0	0	0	INA													

INA = Indicator Not Assessed

HWD = Hazardous Waste Disposed

RWD = Radioactive Waste Disposed

MFR = Materials for recycling

EEE = Exported Electrical Energy

NHWD = Non Hazardous Waste Disposed

CRU = Components for reuse

MER = Materials for energy recovery

ETE = Exported Thermal Energy









CALCULATION RULES

Data quality

Data flows have been modeled as realistically as possible. Data quality assessment is based on the principle that the primary data used for processes occurring at the production site is selected in the first instance. Where this is not available, other reference data is selected from appropriate sources.

Data collection period

The dataset is representative for the production processes used in 2018.

Methodology and reproducibility

The process descriptions and quantities in this study are reproducible in accordance to the reference standards that have been used. The references of all sources, both primary and public sources and literature, have been documented. In addition, to facilitate the reproducibility of this LCA, a full set of data records has been generated which can be accessed via the EcoChain tool. This data portfolio contains a summary of all the data used in this LCA, and correspondingly, in Spenner Erwitte account.



SCENARIOS AND ADDITIONAL TECHNICAL INFORMATION

A1. Raw materials supply

For all purchased materials, relevant Ecolnvent records have been selected.

For modelling reasons, the clinker produced by Spenner and used to make the various types of cement is used as an input product in the LCA of the cement products. Therefore, all impacts allocated to the clinker (purchased materials, incoming transport and processes) are allocated to the A1 section of the cement products.

A2. Transport of raw materials to manufacturer

All incoming transports of the purchased materials are done by truck. Truck transport from the Erwitte production facility to the Duisburg production facility and vice versa are modelled as one-way transports, since these trucks always carry full loads from one plant to the other.

A3. Manufacturing

This module covers the manufacturing of the cement product and includes all processes linked to production such as grinding and internal transportation. Use of electricity, fuels and auxiliary materials related to these processes are properly allocated.









DECLARATION OF SVHC

None of the substances contained in the product are listed in the "Candidate List of Substances of Very High Concern for authorisation", or they do not exceed the threshold with the European Chemicals Agency.



REFERENCES

- EN 15804:2012+A1:2013 Sustainability of construction works. Environmental product declarations. Core rules for the product category of construction products, of 11/2013.
- ISO 14040/14044 on Life Cycle Assessments.
- CEN/TC 51 PCR for cement and building lime, 2015



REMARKS

None

