

Environmental Product Declaration

according to ISO 14025 and EN 15804



This declaration is for:

Spenner CEM II/A-LL 52,5 N

Provided by:

Spenner Zement

spenner



program operator

Stichting MRPI®

publisher

Stichting MRPI®

www.mrpi.nl

MRPI® registration

1.1.00087.2019

EPD registration

00001069

date of first issue

16-12-2019

date of this issue

16-12-2019

expiry date

16-12-2024



Nationale

Milieu DATABASE



PROGRAM OPERATOR

Stichting MRPI®
 Kingsfordweg 151
 1043GR
 Amsterdam

COMPANY INFORMATION

spenner

Spenner Zement
 Hüchtchenweg 2
 59597
 Erwitte
 0049 2943 9860
 info@spenner-zement.de
 https://spenner-zement.de/

SCOPE OF DECLARATION

This MRPI®-EPD certificate is verified by **Niels Jonkers, Ecochain**.
 The LCA study has been done by **Pieter Stadhouders, EcoReview**.
 The certificate is based on an LCA-dossier according to ISO14025 and NEN-EN15804+A1. It is verified according to the 'EPD-MRPI verification protocol May 2017'. EPD's of construction products may not be comparable if they do not comply with NEN-EN15804+A1. Declaration of SVHC that are listed on the 'Candidate List of Substances of Very High Concern for authorisation' when content exceeds the limits for registration with ECHA.

VISUAL PRODUCT



PRODUCT

Spenner CEM II/A-LL 52,5 N

MRPI® REGISTRATION

1.1.00087.2019

EPD REGISTRATION

00001069

DATE OF ISSUE

16-12-2019

EXPIRY DATE

16-12-2024

DECLARED UNIT/FUNCTIONAL UNIT

tonne

DESCRIPTION OF PRODUCT

Portland limestone cement

MORE INFORMATION

DEMONSTRATION OF VERIFICATION

CEN standard EN15804 serves as the core PCR[a]

Independent verification of the declaration and data,
 according to EN ISO 14025:2010:

internal: external: X

(where appropriate[b]) Third party verifier:

Niels Jonkers, Ecochain

[a] Product Category Rules [b] Optional for B-to-B communication,
 mandatory for B-to-C communication (see EN ISO 14025:2010, 9.4).

DETAILED PRODUCT DESCRIPTION

Product name: Spenner CEM II/A-LL 52,5 N

Portland cement combined with ground limestone, sold in bulk quantities. The production processes needed to come to this product are grinding and mixing. The clinker that is used as the main ingredient is self produced. For this, mining, transport, breaking, drying and calcination has been performed.

This product is an intermediate product for making cementitious-bound materials.

COMPONENT (> 1%)	[kg / %]
Anhydrite	3.00%
Iron sulfate	0.40%
Gypsum	1.50%
Limestone	14.10%
Clinker	80.93%
BASF GA 1150 (grinding additive)	0.07%

(*) > 1% van total mass

SCOPE AND TYPE

This product is produced in Erwitte (Germany). It is applied as an intermediate product for cementitious-bound materials.

Analysis has been done using the Ecochain software. Ecoinvent V3.4 was used for the analysis.

It is an intermediate product and therefore end-of-life scenarios are not clear. The specific EPD only covers A1-A3.

PRODUCT STAGE			CONSTRUCTION					USE STAGE					END OF LIFE				BENEFITS AND
			PROCESS										STAGE				LOADS BEYOND THE
			STAGE														SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport gate to site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential	
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D	
x	x	x	MNA	MNA	MNA	MNA	MNA	MNA	MNA	MNA	MNA	MNA	MNA	MNA	MNA	MNA	

X = Module assessed

MNA = Module not assessed

REPRESENTATIVENESS

Not applicable as this is an environmental product declaration for a specific product from a specific manufacturer on a specific location.

ENVIRONMENTAL IMPACT per functional unit or declared unit

	UNIT	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
ADPE	kg Sb-eq.	1.69 E -1	5.39 E -6	1.26 E -1	2.95 E -1	INA													
ADPF	MJ	1.45 E +3	2.91 E +1	2.29 E +2	1.71 E +3	INA													
GWP	kg CO2-eq.	6.71 E +2	1.90 E +0	1.90 E +1	6.92 E +2	INA													
ODP	kg CFC11-eq.	2.59 E -6	3.50 E -7	1.33 E -6	4.28 E -6	INA													
POCP	kg ethene-eq.	6.90 E -2	1.12 E -3	3.27 E -3	7.33 E -2	INA													
AP	kg SO2-eq.	6.31 E -1	8.22 E -3	1.60 E -1	7.99 E -1	INA													
EP	kg (PO4)3--eq.	1.89 E -1	1.64 E -3	3.38 E -2	2.25 E -1	INA													
Toxicity indicators (Dutch market)																			
HTP	kg DCB-eq.	2.07 E +1	7.58 E -1	3.21 E +0	2.47 E +1	INA													
FAETP	kg DCB-eq.	5.78 E -1	2.22 E -2	6.11 E -2	6.61 E -1	INA													
MAETP	kg DCB-eq.	1.55 E +4	8.03 E +1	7.30 E +3	2.29 E +4	INA													
TETP	kg DCB-eq.	4.50 E -1	2.69 E -3	1.12 E -1	5.65 E -1	INA													
ECI	Euro	4.15 E +1	2.24 E -1	2.96 E +0	4.47 E +1	INA													

ADPE = Abiotic Depletion Potential for non-fossil resources

ADPF = Abiotic Depletion Potential for fossil resources

GWP = Global Warming Potential

ODP = Depletion potential of the stratospheric ozone layer

POCP = Formation potential of tropospheric ozone photochemical oxidants

AP = Acidification Potential of land and water

EP = Eutrophication Potential

HTP = Human Toxicity Potential

FAETP = Fresh water aquatic ecotoxicity potential

MAETP = Marine aquatic ecotoxicity potential

TETP = Terrestrial ecotoxicity potential

ECI = Environmental Cost Indicator

RESOURCE USE per functional unit or declared unit

	UNIT	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
PERE	MJ	1.19 E +2	3.99 E -1	1.20 E +2	2.39 E +2	INA													
PERM	MJ	0	0	0	0	INA													
PERT	MJ	1.19 E +2	3.99 E -1	1.20 E +2	2.39 E +2	INA													
PENRE	MJ	1.25 E +3	3.12 E +1	3.34 E +2	1.61 E +3	INA													
PENRM	MJ	0	0	0	0	INA													
PENRT	MJ	1.25 E +3	3.12 E +1	3.34 E +2	1.61 E +3	INA													
SM	kg	0	0	0	0	INA													
RSF	MJ	0	0	0	0	INA													
NRSF	MJ	0	0	0	0	INA													
FW	m3	6.87 E -1	5.61 E -3	8.93 E -2	7.82 E -1	INA													

INA = Indicator Not Assessed

PERE = Use of renewable energy excluding renewable primary energy resources

PERM = Use of renewable energy resources used as raw materials

PENRE = Use of non-renewable primary energy resources excluding non-renewable energy resources used as raw materials

PENRM = Use of non-renewable primary energy resources used as raw materials

SM = Use of secondary materials

NRSF = Use of non renewable secondary fuels

PERT = Total use of renewable primary energy resources

PENRT = Total use of non-renewable primary energy resources

RSF = Use of renewable secondary fuels

FW = Use of net fresh water

OUTPUT FLOWS AND WASTE CATEGORIES per functional unit or declared unit

	UNIT	A1	A2	A3	A1-A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
HWD	kg	2.54 E -2	2.15 E -4	2.92 E -3	2.85 E -2	INA													
NHWD	kg	6.50 E +0	1.79 E +0	1.16 E +0	9.45 E +0	INA													
RWD	kg	2.40 E -3	1.97 E -4	1.78 E -3	4.38 E -3	INA													
CRU	kg	0	0	0	0	INA													
MFR	kg	0	0	0	0	INA													
MER	kg	0	0	0	0	INA													
EEE	MJ	0	0	0	0	INA													
ETE	MJ	0	0	0	0	INA													

INA = Indicator Not Assessed

HWD = Hazardous Waste Disposed

RWD = Radioactive Waste Disposed

MFR = Materials for recycling

EEE = Exported Electrical Energy

NHWD = Non Hazardous Waste Disposed

CRU = Components for reuse

MER = Materials for energy recovery

ETE = Exported Thermal Energy

CALCULATION RULES

Data quality

Data flows have been modeled as realistically as possible. Data quality assessment is based on the principle that the primary data used for processes occurring at the production site is selected in the first instance. Where this is not available, other reference data is selected from appropriate sources.

Data collection period

The dataset is representative for the production processes used in 2018.

Methodology and reproducibility

The process descriptions and quantities in this study are reproducible in accordance to the reference standards that have been used. The references of all sources, both primary and public sources and literature, have been documented. In addition, to facilitate the reproducibility of this LCA, a full set of data records has been generated which can be accessed via the EcoChain tool. This data portfolio contains a summary of all the data used in this LCA, and correspondingly, in Spenner Erwitte account.

SCENARIOS AND ADDITIONAL TECHNICAL INFORMATION

A1. Raw materials supply

For all purchased materials, relevant EcoInvent records have been selected.

For modelling reasons, the clinker produced by Spenner and used to make the various types of cement is used as an input product in the LCA of the cement products. Therefore, all impacts allocated to the clinker (purchased materials, incoming transport and processes) are allocated to the A1 section of the cement products.

A2. Transport of raw materials to manufacturer

All incoming transports of the purchased materials are done by truck. Truck transport from the Erwitte production facility to the Duisburg production facility and vice versa are modelled as one-way transports, since these trucks always carry full loads from one plant to the other.

A3. Manufacturing

This module covers the manufacturing of the cement product and includes all processes linked to production such as grinding and internal transportation. Use of electricity, fuels and auxiliary materials related to these processes are properly allocated.



DECLARATION OF SVHC

None of the substances contained in the product are listed in the “Candidate List of Substances of Very High Concern for authorisation”, or they do not exceed the threshold with the European Chemicals Agency.



REFERENCES

- EN 15804:2012+A1:2013 Sustainability of construction works. Environmental product declarations. Core rules for the product category of construction products, of 11/2013.
- ISO 14040/14044 on Life Cycle Assessments.
- CEN/TC 51 PCR for cement and building lime, 2015



REMARKS

None