
Environmental Product Declaration according to ISO 14025 and EN 15804

This declaration is for: Spenner CEM III/B 42,5 N-LHSR (Erwitte)

Provided by: Spenner Zement



spenner

milieu relevante product informatie

MRPI

program operator Stichting MRPI® publisher Stichting MRPI® www.mrpi.nl

MRPI® registration 1.1.00092.2019 EPD registration 00001074 date of first issue 16-12-2019 date of this issue 16-12-2019 expiry date 16-12-2024









PROGRAM OPERATOR

Stichting MRPI® Kingsfordweg 151 1043GR Amsterdam

COMPANY INFORMATION

spenner

Spenner Zement Hüchtchenweg 2 59597 Erwitte 0049 2943 9860 info@spenner-zement.de https://spenner-zement.de/ PRODUCT Spenner CEM III/B 42,5 N-LHSR (Erwitte)

MRPI® REGISTRATION 1.1.00092.2019

EPD REGISTRATION 00001074

DATE OF ISSUE 16-12-2019

EXPIRY DATE 16-12-2024

DECLARED UNIT/FUNCTIONAL UNIT tonne

SCOPE OF DECLARATION

This MRPI®-EPD certificate is verified by **Niels Jonkers, Ecochain.** The LCA study has been done by **Pieter Stadhouders, EcoReview.**

The certificate is based on an LCA-dossier according to ISO14025 and NEN-EN15804+A1. It is verified according to the 'EPD-MRPI verification protocol May 2017'. EPD's of construction products may not be comparable if they do not comply with NEN-EN15804+A1. Declaration of SVHC that are listed on the 'Candidate List of Substances of Very High Concern for authorisation' when content exceeds the limits for registration with ECHA.

VISUAL PRODUCT



DESCRIPTION OF PRODUCT

Blast furnace slag cement

MORE INFORMATION

https://spenner-zement.de/produkte/zement/port landhuettenzement-cem-iib-s-525-n/



DEMONSTRATION OF VERIFICATION

CEN standard EN15804 serves as the core PCR[a]

Independent verification of the declaration and data,

according to EN ISO 14025:2010:

internal: external: X

(where appropriate[b]) Third party verifier:

Niels Jonkers, Ecochain

[a] Product Category Rules [b] Optional for B-to-B communication, mandatory for B-to-C communication (see EN ISO 14025:2010, 9.4).





DETAILED PRODUCT DESCRIPTION

Product name: Spenner CEM III/B 42,5 N-LHSR

A cement mix, with Ground Granulated Blastfurnace Slag (GGBS) being its largest ingredient, followed by Portland cement. Sold in bulk quantities. The production processes needed to come to this product are grinding and mixing. The clinker that is used for the Portland cement is self produced. For this, mining, transport, breaking, drying and calcination has been performed. The GGBS is also self produced at a different production facility in Duisburg. For its production, drying and grinding had to be performed.

This product is an intermediate product for making cementitious-bound materials.

COMPONENT (> 1%)	[kg / %]
Anhydrite	5.41%
Iron sulfate	0.25%
Gypsum	0.62%
GGBS (Ground Granulated Blastfurnace Slag)	65.30%
Clinker	27.88%
BASF GA 1150 (grinding additive)	0.04%
Limestone	0.10%
Fly ash	0.40%

(*) > 1% van total mass




SCOPE AND TYPE

This product is produced in Erwitte (Germany). It is applied as an intermediate product for cementitious-bound materials.

Analysis has been done using the Ecochain software. Ecoinvent V3.4 was used for the analysis. It is an intermediate product and therefore end-of-life scenarios are not clear. The specific EPD only covers A1-A3.





MNA = Module not assessed

spenner





REPRESENTATIVENESS

Not applicable as this is an environmental product declaration for a specific product from a specific manufacturer on a specific location.

	UNIT	A1	A2	A3	A1-A3	A4	A5	B1	B2	B 3	B4	B5	B6	B7	C1	C2	C3	C4	D
ADPE	kg	2.55	2.57	1.27	3.82	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
	Sb-eq.	E -1	E -5	E -1	E -1									шлл	INA			IINA	
ADPF	MJ	8.88	1.39	2.29	1.26	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
//BIT	IVIS	E +2	E +2	E +2	E +3				INA	INA	INA	INA	INA	INA	INA		INA	INA	
GWP	kg	2.56	9.03	1.90	2.85	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
	CO2-eq.	E +2	E +0	E +1	E +2		INA				INA	11 47 (11 1/ 1			11 1/ 1	
ODP	kg	3.58	1.66	1.33	6.58	INA	INA	INA	INA	INA	INA	INA	A INA	INA	INA	INA	INA	INA	INA
	CFC11-eq.	E -6	E -6	E -6	E -6					INA									
POCP	kg	2.71	5.33	3.27	3.57	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
	ethene-eq.	E -2	E -3	E -3	E -2	INA					INA	INA							
AP	kg	3.25	3.91	1.60	5.25	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
	SO2-eq.	E -1	E -2	E -1	E -1														
EP	kg	8.59	7.82	3.38	1.28	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
L1	(PO4)3eq.	E -2	E -3	E -2	E -1							II NA							
Toxicity	/ indicators (Du	itch mar	ket)																
HTP	kg DCB-eg.	1.24	3.61	3.21	1.93	INA	INA	INA	INA	INA	INA	INA	IA INA	INA	INA	INA	INA	INA	INA
	ку БСБ-еч.	E +1	E +0	E +0	E +1											INA			
FAETP	kg DCB-eq.	2.75	1.06	6.12	4.42	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
	Ky DOD-eq.	E -1	E -1	E -2	E -1									11174	IIN/A	INA			
MAETP	kg DCB-eg.	1.15	3.82	7.31	1.92	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	ΙΝΙΔ
	ку БСБ-ец.	E +4	E +2	E +3	E +4				INA	INA	INA	INA	INA		INA	INA	INA	INA	INA
TETP	kg DCB-eg.	2.21	1.28	1.12	3.47	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
	Ng DOD-eq.	E -1	E -2	E -1	E -1	11174				INA			INA		INA			INA	
ECI	Euro	1.74	1.07	2.97	2.14	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
ECI	Euro	E +1	E +0	E +0	E +1			INA	Ann	INA	Ann	AVII	INA						

ENVIRONMENTAL IMPACT per functional unit or declared unit

ADPE = Abiotic Depletion Potential for non-fossil resources

ADPF = Abiotic Depletion Potential for fossil resources

GWP = Global Warming Potential

ODP = Depletion potential of the stratospheric ozone layer

POCP = Formation potential of tropospheric ozone photochemical oxidants

AP = Acidification Potential of land and water

EP = Eutrophication Potential

HTP = Human Toxicity Potential

FAETP = Fresh water aquatic ecotoxicity potential

MAETP = Marine aquatic ecotoxicity potential

TETP = Terrestrial ecotoxicity potential

ECI = Environmental Cost Indicator







	RESO	URCE	USE	per fu	nctio	າal ເ	unit	or d	ecla	ared	uni	t							
	UNIT	A1	A2	A3	A1-A3	A4	A5	B1	B2	B 3	B 4	B5	B 6	B7	C1	C2	C3	C4	D
PERE	MJ	1.03 E +2	1.90 E +0	1.20 E +2	2.24 E +2	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
PERM	MJ	0	0	0	0	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
PERT	MJ	1.03 E +2	1.90 E +0	1.20 E +2	2.24 E +2	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
PENRE	MJ	8.74 E +2	1.49 E +2	3.35 E +2	1.36 E +3	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
PENRM	MJ	0	0	0	0	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
PENRT	MJ	8.74 E +2	1.49 E +2	3.35 E +2	1.36 E +3	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
SM	kg	0	0	0	0	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
RSF	MJ	0	0	0	0	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
NRSF	MJ	0	0	0	0	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
FW	m3	3.25 E -1	2.67 E -2	8.94 E -2	4.42 E -1	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA

INA = Indicator Not Assessed

PERE = Use of renewable energy excluding renewable primary energy resources

PERM = Use of renewable energy resources used as raw materials

PENRE = Use of non-renewable primary energy resources excluding non-renewable energy resources used as raw materials PENRM = Use of non-renewable primary energy resources used as raw materials SM = Use of secondary materials

NRSF = Use of non renewable secondary fuels

PERT = Total use of renewable primary energy resources

PENRT = Total use of non-renewable primary energy resources RSF = Use of renewable secondary fuels FW = Use of net fresh water

OUTPUT FLOWS AND WASTE CATEGORIES per functional unit or declared unit

	UNIT	A1	A2	A3	A1-A3	A4	A5	B1	B2	B 3	B4	B5	B 6	B7	C1	C2	C3	C4	D
HWD	kg	1.09 E -2	1.03 E -3	2.92 E -3	1.49 E -2	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
NHWD	kg	4.02 E +0	8.54 E +0	1.16 E +0	1.37 E +1	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
RWD	kg	2.07 E -3	9.40 E -4	1.79 E -3	4.80 E -3	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
CRU	kg	0	0	0	0	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
MFR	kg	0	0	0	0	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
MER	kg	0	0	0	0	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
EEE	MJ	0	0	0	0	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA
ETE	MJ	0	0	0	0	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA	INA

INA = Indicator Not Assessed

HWD = Hazardous Waste Disposed

RWD = Radioactive Waste Disposed

MFR = Materials for recycling

EEE = Exported Electrical Energy

NHWD = Non Hazardous Waste Disposed

CRU = Components for reuse

MER = Materials for energy recovery

ETE = Exported Thermal Energy







C

CALCULATION RULES

Data quality

Data flows have been modeled as realistically as possible. Data quality assessment is based on the principle that the primary data used for processes occurring at the production site is selected in the first instance. Where this is not available, other reference data is selected from appropriate sources.

Data collection period

The dataset is representative for the production processes used in 2018.

Methodology and reproducibility

The process descriptions and quantities in this study are reproducible in accordance to the reference standards that have been used. The references of all sources, both primary and public sources and literature, have been documented. In addition, to facilitate the reproducibility of this LCA, a full set of data records has been generated which can be accessed via the EcoChain tool. This data portfolio contains a summary of all the data used in this LCA, and correspondingly, in Spenner Erwitte account.

SCENARIOS AND ADDITIONAL TECHNICAL INFORMATION

A1. Raw materials supply

For all purchased materials, relevant Ecolnvent records have been selected.

For modelling reasons, the clinker produced by Spenner and used to make the various types of cement is used as an input product in the LCA of the cement products. Therefore, all impacts allocated to the clinker (purchased materials, incoming transport and processes) are allocated to the A1 section of the cement products.

The use of GBS (Granulated Blastfurnace Slag) is free of burden. No emissions from the steel production are allocated onto the blast furnace slag. This approach is in accordance with CEN/TC 51 PCR for cement and building lime, 2015.

A2. Transport of raw materials to manufacturer

All incoming transports of the purchased materials are done by truck. Truck transport from the Erwitte production facility to the Duisburg production facility and vice versa are modelled as one-way transports, since these trucks always carry full loads from one plant to the other.

A3. Manufacturing

This module covers the manufacturing of the cement product and includes all processes linked to production such as grinding and internal transportation. Use of electricity, fuels and auxiliary materials related to these processes are properly allocated.







DECLARATION OF SVHC

None of the substances contained in the product are listed in the "Candidate List of Substances of Very High Concern for authorisation", or they do not exceed the threshold with the European Chemicals Agency.

REFERENCES

• EN 15804:2012+A1:2013 Sustainability of construction works. Environmental product declarations. Core rules for the product category of construction products, of 11/2013.

- ISO 14040/14044 on Life Cycle Assessments.
- CEN/TC 51 PCR for cement and building lime, 2015



REMARKS None

